


Technical Data Pressed Steel Grille

P6800 Pressed Steel Air Transfer



Ac (M ²)	Af (M ²)	APERTURE A x B (mm)	Vf (M/S) P _{Sn} (Pa)	1.00	1.25	1.50	2.00	2.50	3.00	3.50
				3	5	7	10	14	20	28
0.015	0.011	150 x 100	I/s	15	19	23	30	38	45	53
			NC	-	-	-	-	-	18	53
0.021	0.017	150 x 150	I/s	21	27	32	42	53	63	73
		200 x 100	NC	-	-	-	-	-	18	20
0.026	0.018	250 x 100	I/s	26	33	39	52	65	78	91
			NC	-	-	-	-	-	18	21
0.031	0.022	200 x 150	I/s	31	39	47	62	78	93	109
		300 x 100	NC	-	-	-	-	-	18	21
0.040	0.030	200 x 200	I/s	40	50	60	80	100	120	140
		250 x 150	NC	-	-	-	-	-	19	23
0.046	0.034	300 x 150	I/s	46	57	69	92	115	138	161
			NC	-	-	-	-	-	19	23
0.050	0.039	250 x 200	I/s	50	63	75	100	125	150	175
		350 x 150	NC	-	-	-	-	-	19	25
0.065	0.048	250 x 250	I/s	65	81	98	130	163	195	228
		300 x 200 400 x 150	NC	-	-	-	-	-	19	25
0.072	0.056	350 x 200	I/s	72	90	108	144	180	216	252
			NC	-	-	-	-	-	20	26
0.078	0.060	300 x 250	I/s	78	98	117	156	195	234	273
		400 x 200	NC	-	-	-	-	-	20	26
0.093	0.073	300 x 300	I/s	93	116	140	186	230	279	326
		350 x 250 450 x 200 600 x 150	NC	-	-	-	-	-	21	27
0.105	0.086	350 x 300	I/s	105	131	158	210	263	315	368
		400 x 250 500 x 200	NC	-	-	-	-	-	21	27
0.116	0.088	450 x 250	I/s	116	145	174	232	290	348	406
			NC	-	-	-	-	17	22	28
0.125	0.099	350 x 350	I/s	125	156	188	250	313	375	438
		400 x 300 500 x 250 600 x 200	NC	-	-	-	-	18	23	29
0.145	0.113	400 x 350	I/s	145	181	218	290	363	435	508
		450 x 300	NC	-	-	-	-	18	23	29
0.165	0.124	400 x 400	I/s	165	206	248	330	413	495	578
		450 x 350	NC	-	-	-	-	18	24	30
0.186	0.143	450 x 400	I/s	186	233	279	372	465	558	651
		500 x 350 600 x 300	NC	-	-	-	17	19	26	32
0.209	0.161	450 x 450	I/s	209	261	314	418	523	627	732
		500 x 400 600 x 350	NC	-	-	-	17	21	27	34
0.258	0.199	500 x 500	I/s	258	323	387	516	645	774	903
		600 x 400	NC	-	-	16	20	24	30	38